

**TECHNICAL DATA SHEET
THINNER FOR BASECOATS**The identification code: E-RB
Line: EXLAK**PRODUCT DESCRIPTION**

A mixture of properly selected organic solvents used for diluting basecoats with metallic and pearl effect. It is fully compatible with all basecoats in our market. Specially selected solvents allow excellent application of layer of basecoat on the surface and correct placement of aluminium tiles before the complete evaporation.

USAGE

- basecoats with metallic effect
- basecoats with pearl effect
- basecoats with non-metallic effect

TYPES OF THINNER

Type	Conditions	Description
Slow	> 28°C or large surfaces (for example: industrial)	Specially selected solvents allow excellent application of layer of basecoat on surfaces in rooms, where there is high temperature. Thinner does not evaporate between the gun nozzle and painted surface preventing so-called „dusting“ of basecoat.
Standard WB-50	≤ 28°C	The composition of suitable solvents allows for spraying basecoat for car body parts at temperatures up to 28°C.

APPLICATION CONDITIONS

Ready for use.

RULES OF CONDUCT WHEN APPLYING

Thinner for basecoats pour directly to prepared basecoat.

STORAGE TIME AND CONDITIONS

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 12 months from date of manufacture - date on the top of container.

HEALTH AND SAFETY REGULATIONS

See Safety Data Sheet of the product.

SPECIFIC WEIGHT

About 0.9 g/cm³