

## TECHNICAL DATA SHEET


### CLEARCOAT SPEED HS 760

The identification code: E-LBHSS760  
Line: EXLAK




#### PRODUCT DESCRIPTION

Clearcoat SPEED HS 760 is a High-Solid two-component acrylic clearcoat in **SPEED LINE** with very low content of volatile organic compounds and very short time of curing of clearcoat coating. It's very resistant to UV rays. It has an excellent flow and very high gloss giving the surface a great look.

#### MIXING RATIO

	<b>A:</b> Clearcoat SPEED HS 760 (HS SPEED LP2) [code: E-LBHSS760]	100
	<b>B:</b> Hardener SPEED HS 760 (HS SPEED LP2) [code: E-UHSS760]	50
Comments:	Use without thinner or 0-5 % acrylic thinner.	

#### APPLICATION

	Number of layers	1,5
	Pressure	2 - 2,5 bar
	Nozzle	1.3 - 1.4 mm
	Flash off between layers	8-10 min
	Mixture life after mixing clearcoat with standard type of hardener	60 min at 20°C

**The first half-layer** of clearcoat should be applied on the pre-dried layer of basecoat.

**Second layer** of clearcoat should be applied as a **full layer** and left to complete flow and hardening.



In case of using spraying booth, after second layer painter should wait 10 minutes and after that time turn on spray booth on 50°C heating level.

## TECHNICAL DATA SHEET

### CLEARCOAT SPEED HS 760

The identification code: E-LBHSS760  
Line: EXLAK

#### ADDITIONAL INFORMATION

	Viscosity (DIN 4/20°C)	19 – 21,5 s
	Operating hardness	3-4 h at 20°C 15 min at 50°C
	Ending hardness	4 days
	Dust dry	20-30 min at 20°C -

#### CONTENT OF VOLATILE ORGANIC COMPOUNDS

Maximum content of VOC in product	490 g/l
VOC for category: II,B/d	840 g/l

*Clearcoat complies standards of EU Directive 2004/42/CE/II,B/e(840)*

#### GLOSS

Output gloss	98°
--------------	-----

#### STORAGE TIME AND CONDITIONS

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 12 months from date of manufacture - date on the top of container.

#### CLEANING EQUIPMENT

For cleaning equipment can be used acryl thinner or nitro thinner. It is recommended to use thinner for cleaning paint spray guns.

#### HEALTH AND SAFETY REGULATIONS

See Safety Data Sheet of the product.

#### SPECIFIC WEIGHT

About 1.0 g/cm<sup>3</sup>